

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An apparatus for protecting a door gasket of a refrigerator, comprising:

a drawer body ~~with including~~ a storage space capable of being configured to be put in
into and taken out from of a main body of ~~the~~ a refrigerator;

a door ~~which is connected~~ coupled to one side of the drawer body and configured to be
pivotal on pivot about an axis of rotation ~~and of which a back is positioned proximate one~~
end portion of the door, wherein an inner peripheral surface comes into close contact with of
the door is configured to align with a front face of the main body of the refrigerator ~~in a state~~
~~where when~~ the drawer body is put positioned in the main body of the refrigerator;

a gasket ~~provided~~ disposed between the axis of rotation and an edge portion of the one
end portion of the door, wherein the gasket is configured to be positioned between the
periphery of the back inner peripheral surface of the door and the front face of the main body of
the refrigerator when the drawer body is positioned in the main body of the refrigerator and the
door is in a closed position; and

Serial No. 10/698,382
Amdt. dated October 21, 2005
Reply to Office Action of July 21, 2005

Docket No. IK-0068

a cushioning member ~~disposed below~~ positioned between the gasket and the edge portion of the one end portion of the door, wherein the cushioning member is configured to prevent contact over compression of the gasket with the main body of the refrigerator when the door pivots on about the axis of the rotation.

2. (Currently Amended) The apparatus as claimed in claim 1, wherein the cushioning member ~~is a~~ comprises at least one roller.
3. (Currently Amended) The apparatus as claimed in claim 1, wherein the cushioning member is configured to be installed on the door.
4. (Currently Amended) The apparatus as claimed in claim 1, wherein the cushioning member is configured to be installed on the main body of the refrigerator.

5. (Currently Amended) The apparatus as claimed in claim 1, wherein the gasket is ~~formed~~
~~below the axis of rotation~~installed on the door.

6. (Currently Amended) The apparatus as claimed in claim 1, wherein the cushioning
member comprises a plurality of cushioning members~~are installed below the gasket~~rollers.

7. (New) The apparatus of claim 1, wherein the axis of rotation is substantially coincident
with a position of a hinge pin which couples a lower end of the door to a lower portion of the
drawer body.

8. (New) The apparatus of claim 7, wherein an upper end of the door is configured to pivot
about the hinge pin such that the upper end of the door tilts outward and downward as the door
is opened.

9. (New) The apparatus of claim 2, wherein the at least one roller is configured to provide
rolling contact between the door and the front face of the main body as the door pivots about
the axis of rotation.

10. (New) The apparatus of claim 9, wherein the rolling contact provided by the at least one roller prevents compression of the gasket between the door and the main body as the door pivots about the axis of rotation.

11. (New) A device configured to protect a door gasket, comprising:

a door coupled to an apparatus and configured to pivot about an axis of rotation;

a hinge pin that couples the door and the apparatus so that the door can pivot about an axis of rotation defined by the hinge pin;

a gasket provided between a surface portion of the door facing an interior of the apparatus, and between the hinge pin and an outer edge of the door; and

a cushioning member positioned between the gasket and the outer edge of the door, wherein the cushioning member is configured to preclude over compression of the gasket as the door pivots.

12. (New) The device of claim 11, wherein the gasket is configured to form a seal between the surface portion of the door facing the interior portion of the apparatus and a front face of the apparatus when the door is in a closed position.

13. (New) The device of claim 11, wherein the cushioning member comprises at least one roller configured provide rolling contact between the door and the front face portion of the apparatus as the door pivots about the hinge pin.

14. (New) The device of claim 13, wherein the rolling contact provided by the at least one roller prevents compression of the gasket between the door and the apparatus as the door pivots about the hinge pin.

15. (New) The device of claim 11, wherein the cushioning member comprises a plurality of rollers installed on the door.

16. (New) The device of claim 11, wherein the cushioning member comprises at least one roller installed on the apparatus.

17. (New) The device of claim 11, wherein the apparatus comprises a refrigerator.

18. (New) The device of claim 17, wherein the apparatus comprises a drawer type refrigerator, and wherein the door is coupled to a drawer body configured to slide into and out of a receiving space of the drawer type refrigerator.

Serial No. 10/698,382

Docket No. IK-0068

Amdt. dated October 21, 2005

Reply to Office Action of July 21, 2005

19. (New) The device of claim 18, wherein the door is configured to rotate about a lower end portion thereof such that an upper portion of the door pivots outward and downward as the door is opened.

20. (New) A drawer type refrigerator comprising the device of claim 11.